DECLARATION OF PERFORMANCE

No13-SC-B15

Product Type/Identification: 10.4 Dense Midi

Intended Use: in walls, columns & partitions

Manufacturer Stowell Concrete Ltd

Arnolds Way Yatton North Somerset BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4
Harmonised Standard: EN771-3:2011
ETA: Not relevant

Declared Performance:

	Performance		Harmonised	
Essential Characteristics			Technical	
			Specification	
	Lengths	440mm	290mm	
Dimensions	Width	140mm		
	Heights	140mm	215mm	
	Tolerance category	D1		
	Shape and features	Solid		
Configuration	Group according to	Group 1		EN771-3:2011
	EN 1996-1-1 (EC6)			
Compressive strength	Mean compressive	10.4N/mm²		
	strength			
	Direction of load	Perpendicular to		
		bed faces		
	Unit category	Category II		
Dimensional stability		<0.4mm/m		
	Shear bond strength	0.15N/mm ² Ta	bulated value	
Bond strength	Flexural bond strength	NPD		
Reaction to fire		A1		
Water absorption		<8g/m²/s		
Water vapour permeability		5/15 Tabulated value		
	Gross density	2050kg/m³		
Direct airborne sound	Configuration;			
Insulation	dimensions and	See configuration		
	tolerances			
Thermal conductivity		1.06 (λ 10, dry unit) W/mK		
Durability against freeze thaw		Pass		
Dangerous substances		NPD		

This declaration of performance is issued under the sole responsibility of the manufacturer above. Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell

Managing Director 1st July 2013.