

DECLARATION OF PERFORMANCE

No13-SC-K06



Product Type/Identification: Hydraulically pressed Fluted Channel
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd
Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant

Declared Performance:

| Essential Characteristics | | Performance | Harmonised Technical Specification | |
|---------------------------|--------------------|----------------------------------|------------------------------------|--|
| Dimensions | Lengths | 913mm | EN1340:2003 | |
| | Widths | 255mm | | |
| | Heights | 75mm | | |
| | Tolerance category | 2 | | |
| Bending strength | | 3.5Mpa | | |
| Slip/skid resistance | | Satisfactory | | |
| Reaction to fire | | A1 | | |
| External fire performance | | Satisfactory | | |
| Thermal conductivity | | 1.52 ($\lambda_{10, dry}$)W/mK | | |
| Durability | | Pass | | |
| Emission of Asbestos | | No content | | |

This declaration of performance is issued under the sole responsibility of the manufacturer above.

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
Managing Director 1st July 2013.